

Bambu Lab H2S 3D Printer (Global Version)

LKR 761,388.00



- **6-Month Warranty included** for worry-free operation.
- **Large 340 x 320 x 340 mm Build Volume** – ideal for printing big, detailed models without the need for splitting.
- **Ultra-Fast Print Speed** up to 1,000 mm/s with 20,000 mm/s² acceleration for

exceptional productivity.

- **High-Temperature Capability** – all-metal hotend up to 350°C and heated bed up to 120°C for professional-grade materials.
- **Advanced Smart Features** – equipped with 23+ sensors, heated chamber, and built-in camera for stable, intelligent printing.

Bambu Lab H2S 3D Printer (Global Version)

High-Performance, Big-Reach Printing

Imagine a 3D printer that doesn't hold back; you've got big build volumes, blistering speeds, and clean, enclosed chambers all in one sleek machine. The **Bambu Lab H2S 3D Printer (Global Version)** ups the game with a full 340 × 320 × 340 mm build area, meaning you can tackle large projects without splitting them into parts. If you've been waiting for a 3D printer that feels more like a mini-factory than a hobbyist tool, you're in the right place. At *Master3D*, we're proud to offer this powerhouse that blends productivity, reliability and versatility.

Alongside the volume boost, you'll find a Core XY motion system paired with a servo-driven extruder that's built for serious flow. Think faster print times and more confident results.

Smart Safety & Material Freedom

Safety and ease-of-use aren't afterthoughts here. The H2S packs 23+ sensors, multiple cameras and an advanced airflow/heated chamber system, so you can print everything from PLA to PA and carbon-fibre-reinforced filaments with fewer worries. And yes, the H2S supports a max nozzle temp of 350 °C and a 120 °C heated bed, making it solid for engineering materials.

If you've been looking for "that one printer" that gives you room to grow and doesn't lock you into just basic plastics, the Global version of this printer is a serious upgrade on many entry machines.

Key Specs to Know

- Build volume: **340 × 320 × 340 mm**
- Max nozzle temp: **350 °C** and bed temp to **120 °C**
- Max toolhead speed: **1 000 mm/s**, acceleration: **20 000 mm/s²**
- Full-metal hotend + hardened-steel nozzle (supports 0.2-0.8 mm)

- Chamber heating (up to ~65 °C) + advanced filtration for printing high-end materials

So if you're ready to step up your printing game, the **Bambu Lab H2S 3D Printer (Global Version)** at *Master3D* is definitely worth a look.

FAQ

1. Q. Does the H2S handle multi-material printing (like color or dual-nozzles)?

A. This version is a single-nozzle machine (hence "S"), so while it supports a wide range of materials and large builds, it's not designed for simultaneous dual-nozzle multi-material like some high-end units.

2. Q. Is the “Global Version” different from other regional models?

A. Yes—the Global Version often includes compatibility for 200-240 V mains, broader WiFi bands, and firmware ready for international use. Always check local support and warranties.

3. Q. What kind of materials can I use with this printer?

A: Loads. From basic PLA and PETG to ABS, ASA, PC, PA, even carbon-glass-fibre-reinforced filaments—this machine gives you serious material flexibility.

Category	Specification
Model Name	Bambu Lab H2S 3D Printer (Global Version)
Build Volume	340 x 320 x 340 mm
Machine Dimensions	486 x 462 x 570 mm
Machine Weight	Approx. 24.5 kg
Frame Construction	All-metal enclosed frame
Motion System	CoreXY with Servo-driven extruder
Max Print Speed	1,000 mm/s
Acceleration	20,000 mm/s ²
Layer Resolution	0.1 – 0.4 mm
Nozzle Diameter Options	0.2 mm, 0.4 mm, 0.6 mm, 0.8 mm
Max Nozzle Temperature	350°C
Max Bed Temperature	120°C
Chamber Heating	Up to ~65°C
Extruder Type	Direct drive with servo control
Hotend Material	Full metal with hardened steel nozzle
Filament Diameter	1.75 mm

Category	Specification
Compatible Materials	PLA, PETG, ABS, ASA, TPU, PC, PA, PA-CF, PA-GF, PET-CF, and more
Build Plate Type	Magnetic flexible PEI plate
Auto Bed Leveling	Yes, advanced multi-point calibration
Cooling System	Dual fan setup for model and hotend
Filament Runout Sensor	Yes
Power Loss Recovery	Supported
Connectivity Options	Wi-Fi, LAN, USB
Control Interface	7-inch IPS Touchscreen
Supported File Formats	3MF, STL, OBJ, AMF, G-code
Supported Software	Bambu Studio, OrcaSlicer (compatible)
Operating Noise Level	< 45 dB (typical)
Operating Voltage	200V - 240V (Global Version)
Safety Features	23+ onboard sensors, thermal protection, filament detection, door safety sensor
Camera Monitoring	Yes - built-in monitoring camera
Filter System	Active carbon filtration system for fumes
Operating System Compatibility	Windows, macOS

Disclaimer: Specifications, dimensions, and weight are approximate and may vary slightly due to manufacturing tolerances or regional variations. Images are for reference only and may differ from the actual product appearance.