

# Bambu Lab P1P 3D Printer (China Mainland Version)

**LKR 284,100.00**



- **6-Month Warranty included** for worry-free operation.
- **Rapid printing speed** of up to 500mm/s.
- **Spacious build volume:** 256 × 256 × 256 mm<sup>3</sup> for large projects.

Property of Master3D (PVT) LTD. Visit <https://www.master3d.lk>

- **Automatic bed levelling** for seamless printing setup.
- **Versatile filament compatibility**, including PLA, PETG, TPU, PVA, PET, and more.

## **Bambu Lab P1P 3D Printer (China Mainland Version): Redefine Your Printing Journey**

Step into the future of 3D printing with the **Bambu Lab P1P 3D Printer**. Designed to cater to the needs of both novices and seasoned makers, this printer offers a blend of precision, speed, and ease of use. This model is perfect for those who seek high-quality prints and efficient performance. At *Master3D*, we proudly present this innovative machine that will elevate your 3D printing experience.

### **Cutting-Edge Technology and Unmatched Precision**

The **Bambu Lab P1P 3D Printer** stands out with its FDM printing technology, delivering top-notch prints every time. With a spacious build volume of  $256 \times 256 \times 256 \text{ mm}^3$ , you have ample room to bring your creative ideas to life. The maximum hot end temperature of  $300^\circ\text{C}$  and an all-metal hotend ensure the versatility to work with various filaments, while the stainless steel nozzle guarantees durability.

### **Impressive Features for Superior Performance**

*Master3D* is excited to offer a printer packed with features that ensure exceptional results:

- **Printing Speed:** Up to 500mm/s
- **Build Volume:**  $256 \times 256 \times 256 \text{ mm}^3$
- **Auto Leveling:** Yes
- **Filament Compatibility:** Ideal: PLA, PETG, TPU, PVA, PET; Capable (Enclosure required): PA, PC, ABS, ASA
- **Max Build Plate Temperature:**  $100^\circ\text{C}$

### **Versatility and Convenience**

The **Bambu Lab P1P 3D Printer** is designed for ease of use and flexibility. Its automatic bed leveling and customizable side panels make it a versatile choice for any project. With support for up to 16 colors (AMS required) and timelapse

capability, this printer ensures your prints are not only high-quality but also visually stunning. At *Master3D*, we guarantee a machine that caters to all your 3D printing needs.

## FAQs

1. **Q. What filaments are compatible with the Bambu Lab P1P 3D Printer?**

A. The **Bambu Lab P1P 3D Printer** supports PLA, PETG, TPU, PVA, PET as ideal filaments, and with an enclosure, it can handle PA, PC, ABS, and ASA.

2. **How easy is it to set up the Bambu Lab P1P 3D Printer ?**

A. The **Bambu Lab P1P 3D Printer** can be set up in just 15 minutes, thanks to its user-friendly design.

3. **Does the Bambu Lab P1P 3D Printer (China Mainland Version) support cloud printing?**

A. This version does not support connection to the Bambu Lab cloud; it only allows printing via an SD card or through LAN mode.

Get your hands on the **Bambu Lab P1P 3D Printer** at *Master3D* and transform your 3D printing experience. Ready to bring your ideas to life? The **Bambu Lab P1P 3D Printer** is your perfect partner in creativity!

Specification	Details
<b>Version</b>	China Mainland Version
<b>Build Volume</b>	256 × 256 × 256 mm <sup>3</sup>
<b>Nozzle</b>	Stainless Steel
<b>Hotend</b>	All-Metal
<b>Max Hot End Temperature</b>	300°C
<b>Filament Diameter</b>	1.75 mm
<b>Chamber Monitoring Camera</b>	Low Rate Camera 1280 x 720 / 0.5fps
<b>Timelapse</b>	Supported
<b>Supported Filament</b>	Ideal: PLA, PETG, TPU, PVA, PET; Capable (Enclosure required): PA, PC, ABS, ASA
<b>Build Plate Surface Compatibility</b>	Bambu Cool Plate, Bambu Engineering Plate, Bambu High Temperature Plate
<b>Max Build Plate Temperature</b>	100°C
<b>Max Speed of Tool Head</b>	500 mm/s
<b>Max Acceleration of Tool Head</b>	20 m/s <sup>2</sup>

Specification	Details
<b>Physical Dimensions</b>	386 × 389 × 458 mm <sup>3</sup>
<b>Package Dimensions</b>	485 × 480 × 528 mm <sup>3</sup>
<b>Net Weight</b>	9.65 kg
<b>Gross Weight</b>	14.3 kg
<b>Electrical Requirements</b>	100-240 VAC, 50/60 Hz, 1000W@220V, 350W@110V
<b>Multi-Color Printing</b>	Up to 16 Colors (AMS required)
<b>Automatic Bed Leveling</b>	Yes
<b>Setup Time</b>	15 minutes
<b>Customization</b>	Customizable side panels

**Disclaimer:** Dimensions and weight may vary. Images are for reference only.